

WET LISTED LED PAR LAMPS PAR38 SERIES



PRODUCT DESCRIPTION:

MaxLite introduces Wet Listed 15 watt LED replacements for 120 watt incandescent PAR38 lamps. Ideal for indoor and outdoor applications including wet locations.

FEATURES:

- Wattage: 15W
- Lumens: 1,250
- Equivalent: 120W Inc.
- Volts: 120V
- Hertz: 60Hz
- Beam angle: 40°
- CRI: ≥82
- Power factor: 0.90
- Dimmable down to 10%
- ENERGY STAR certified
- Operating temperature range: -4° to 104° F
- Life Hours: 25,000 Hrs @ L70 standard
- Not suitable for use in enclosed luminaires
- Suitable for damp or wet locations
- Five year warranty

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: 15P38WDLED30FL

15P38W	DLED	FL	
FAMILY	DIMMABILITY	COLOR TEMPERATURE (CCT)	BEAM ANGLE
15P38W= 15 Watts, PAR38 Wet Rated	DLED= Dimmable	27= 2700K 30= 3000K	FL= Flood 40°

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL
AH	SDM3/1000/WHITE
AH	SDM/600/WHITE
CTL	DM600-12-3
LEVITON	6631-LA
	S-600P-WH
	603-6631-A
	6631-A
	IPL06

MAKE	DIMMER MODEL
LEVITON	IPI10
	6631-LW
	6683-IW
LUTRON	DV-603P
	S-600
	DVWCL-153PH-WH
	DV-603PH-WH
	S-600H-WH

MAKE	DIMMER MODEL
LUTRON	D-600RH-DK
	TG-600PH-IV
	D-600R-IV
	DVCL-153P-WH
	S-603PH-WH
	DVCL-153P
	LGCL-153P
	CTCL-153P

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

SPECIFICATIONS:

15P38WDLEDxxFL

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Wattage	15W
	Color Temperature	2700K, 3000K
	Lumens Delivered (lm)	1,250
	Efficacy (lm/w)	83
	Equivalency	120W Inc.
	Lumen Maintenance (L70)	25,000 hours
ELECTRICAL	Power Factor	≥0.90
	Input Voltage	120V
PHYSICAL	Operating Temperature	-4° F to 104° F
APPLICATION	Environment	Dry, Damp, Wet
	Warranty	5 Year

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTAGE	INCANDESCENT EQUIVALENCY	CRI	OUTPUT (LUMENS)	CBCP (cd)	CCT	BEAM ANGLE	DIMENSIONS MOL" X W"
1408269	15P38WDLED27FL	★	15W	120W	82	1250	2444	2700K	40°	5.16" x 4.73"
1408270	15P38WDLED30FL	★	15W	120W	83	1250	2385	3000K		

★ ENERGY STAR certified