

**WET LISTED LED PAR LAMPS**  
**PAR38 SERIES**



**PRODUCT DESCRIPTION:**

MaxLite introduces Wet Listed 17 watt LED replacements for 150 watt incandescent PAR38 lamps. Ideal for indoor and outdoor applications including wet locations.

**FEATURES:**

- Wattage: 17W
- 120V / 60Hz
- Available in 40° flood
- L70 standards: 25,000 Hrs
- CRI: >80
- High output chip-on-board LED
- Dimmable down to ten percent
- ENERGY STAR certified for item 17P38DLED27FL and 17P38DLED30FL
- Operating temperature range: -4° to 104° F
- Not for use in enclosed luminaires
- Five year warranty

**MODEL SELECTION** (Full list of order codes on pg. 2)

Typical order example: 17P38DLED30FL

| 17P38                  | DLED           |  | FL            |
|------------------------|----------------|--|---------------|
| FAMILY                 | DIMMABILITY    | COLOR TEMPERATURE (CCT)                          | BEAM ANGLE    |
| 17P38= 17 Watts, PAR38 | DLED= Dimmable | 27= 2700K<br>30= 3000K<br>41= 4100K<br>50= 5000K | FL= Flood 40° |

**COMPATIBLE DIMMERS:**

| MAKE   | DIMMER MODEL | MAKE    | DIMMER MODEL |
|--------|--------------|---------|--------------|
| Lutron | CTCL-153P    | Leviton | IPL06        |
| Lutron | DVCL-153P    | Leviton | IP110        |
| Lutron | LGCL-153P    | Leviton | 6631-LW      |
| Lutron | S-600        | Leviton | 6683-IW      |

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

**SPECIFICATIONS:**

|                            |                         | PAR38                      |
|----------------------------|-------------------------|----------------------------|
| ITEM                       | SPECIFICATION           | 17 WATTS                   |
| <b>GENERAL PERFORMANCE</b> | Color Temperature       | 2700K, 3000K, 4100K, 5000K |
|                            | Lumens Delivered (lm)   | 1300                       |
|                            | Efficacy (lm/w)         | 76                         |
|                            | Equivalency             | 150W                       |
|                            | Lumen Maintenance (L70) | 25,000 hours               |
| <b>ELECTRICAL</b>          | Power Factor            | ≥0.90                      |
|                            | Input Voltage           | 120V                       |
| <b>PHYSICAL</b>            | Operating Temperature   | -4° F to 104° F            |
| <b>APPLICATION</b>         | Environment             | Dry, Damp, Wet             |
|                            | Warranty                | 5 Year                     |

**ORDERING:**

| ORDER CODE | MODEL         | ENERGY STAR | WATT | INCANDESCENT EQUIVALENCY | CRI | OUTPUT (LUMENS) | CBCP (cd) | DIMENSIONS (MOL" x W") | CCT   | BEAM ANGLE |
|------------|---------------|-------------|------|--------------------------|-----|-----------------|-----------|------------------------|-------|------------|
| 73654      | 17P38DLED27FL | ★           | 17W  | 150W                     | 80  | 1300            | 3155      | 5.10" x 4.75"          | 2700K | 40°        |
| 73656      | 17P38DLED30FL | ★           | 17W  | 150W                     | 80  | 1300            | 3255      | 5.10" x 4.75"          | 3000K | 40°        |
| 73658      | 17P38DLED41FL |             | 17W  | 150W                     | 80  | 1300            | 4125      | 5.10" x 4.75"          | 4100K | 40°        |
| 73696      | 17P38DLED50FL |             | 17W  | 150W                     | 80  | 1300            | 4610      | 5.10" x 4.75"          | 5000K | 40°        |

★ ENERGY STAR certified