

COMMERCIAL DOWNLIGHT RETROFITS
2700K



PRODUCT DESCRIPTION:

The commercial-grade LED Recessed Downlight Retrofit is supplied with a quick connect-case and conduit to make an easy connection to an existing recessed fixture frame junction box.

FEATURES:

- Universal voltage (120-277)
- Mounts into existing recessed frame
- Supplied with optional retaining clips if existing frame does not have adequate friction springs to secure reflector
- cETL listed for damp location use
- CRI: > 80
- PF: >.9
- Five year limited warranty
- Dimmable to 5% (120v only)

CONSTRUCTION:

- Supplied with a heavy gauge anodized aluminum reflector in a haze finish
- External driver for easy retrofit and maintenance
- Power supply features integral thermal protection



Scan the QR code with a smartphone to view the installation video or visit the following link: <http://bit.ly/ledcrdr>

*V2 only pertains to the 15W product

COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL
Lutron	CTCL-153PD*
Lutron	DVCL-153PL*
Lutron	CTELV-303P
Lutron	LGCL-153PL*
Leviton	IPI10

* Dimming control should be adjusted to 5% minimum light output level in order to avoid flickering. Please consult dimming control Instruction manual for specific procedure.

SPECIFICATIONS:

ITEM	SPECIFICATION	RR62327W	RR62627W	RR81527W/V2	RR82327W	RR82627W	RR93027W
		DETAILS					
GENERAL PERFORMANCE	Power Consumption (W)	23W	26W	15W	23W	26W	30W
	Lumens Delivered (lm)	1,360	1,300	850	1,360	1,450	2,065
	Efficacy (lm/W)	59.1	50.0	56.7	59.1	55.8	68.8
	Color Temperature	2700K					
	L70 Lifetime (hours)	50,000					
	CRI	> 80					
	Color Consistency	Proprietary binning for uniform color					
ELECTRICAL	Power Factor	.90					
	Input Voltage	120-277V standard					
	Compatible Dimmers	Lutron CTCL-153PD, DVCL-153PL, CTELV-303P, DVELV-303P, LGCL-153PL; Leviton IPI10					
PHYSICAL	Weight	2.4-2.6 lbs					
	Mounting	Mounts into existing recessed frame					
	Operating Temperature	0° – 104° F					
	Humidity	20% - 85% RH, non-condensing					
CERTIFICATION	Certification	Energy Star (select models), FCC, ETL					
	Material Usage	RoHS compliant; no mercury					
	Environment	Indoor					
	Warranty	5 years					

ORDERING*:

ORDER CODE	MODEL	SIZE	WATTAGE	CCT	ENERGY STAR QUALIFIED
101254	RR62327W	6"	23W	2700K	Yes
74622	RR62627W*	6"	26W		No
101648	RR81527W/V2	8"	15W		Yes
76933	RR82327W	8"	23W		Yes
74220	RR82627W*	8"	26W		No
76934	RR93027W	9"	30W		Yes

*Please contact your MaxLite representative to order products that don't have order codes listed here.
*RR62627W and RR82627W are not Energy Star qualified.

REFLECTOR DIMENSIONS:

	6" MODELS	7" MODELS	8" MODELS
REFLECTOR DIAMETER	6.4"	7.9"	9.5"
REFLECTOR HEIGHT	4.8"	5.6"	7.2"