


LED STRIP
LS GEN 2 SERIES



DIMENSION:



PRODUCT DESCRIPTION:

The new 8' LED linear strip offering with its dome lens can be the illumination solution in commercial, industrial, retail and residential applications. Fixtures can be used in coves, parking facilities, shops, task and general area lighting where 8' solution is required.

FEATURES:

- 0-10V dimming standard
- Power factor >0.9
- CRI>80
- Universal voltage 120-277V
- Operating Temperature: -4°F to 104°F
- Suitable for Damp locations
- Operating humidity 10% to 80% RH non-condensing
- Sensor and Emergency option

CONSTRUCTION:

- Sheet metal housing
- Powder Coated
- One piece (PC) Polycarbonate lens
- Stainless steel mounting kits

WARRANTY:

10-year standard warranty with labor allowance* (further details available at www.maxlite.com/warranties)
*Warranty Limitations: Product must be rated for the application per the Product Data Sheet (PDS); operated < 16 hrs; in ambient of -4°F to 104°F.

*Up to \$25/unit; labor allowances of up to \$500/unit available for purchase – contact MaxLite representative for details.



FAMILY	SIZE	WATTAGE (NOMINAL)	VOLTAGE	CCT	
LS2= Linear Strip Gen 2	96= 8ft	65= 65W 90= 90W	U= 120-277V	40= 4000K 50= 5000K	(OMIT)= None MS= Bi-Level Motion Sensor with Daylight Harvesting and Remote Control Capability EM= Battery Backup Unit

NOTES:

1. EM and EMMS are not DLC listed.

SPECIFICATIONS:



SPECIFICATIONS:		LS2-9665U-XX	LS2-9690U-XX
ITEM	SPECIFICATION	DETAILS	
GENERAL PERFORMANCE	Power Consumption (W)	65	90
	Lumens Delivered (lm)	8,580	11,995
	Efficacy (lm/W)	133	134
	CRI	≥80	
	Color Temperature (K)	4000K, 5000K	
	L70 Lifetime (hours)	>100,000 hours at 40°C	
	Color Consistency	Proprietary binning for uniform color	
ELECTRICAL	Power Factor	>0.9	
	Input Voltage	120-277V	
PHYSICAL	Mounting	Fixture can be surface, pendant, or suspension mounted	
	Operating Temperature	-4° to 104° F	
	Humidity	10% of 80% RH, non-condensing	
QUALIFICATIONS	Qualifications	DLC Premium, cULus, FCC	
	Material Usage	RoHS compliant; no mercury	
	Environment	Indoor/Damp	
	Warranty	5 Years	

4000K Performance Data Values

ORDERING:

MODEL NUMBER	WATTAGE	CCT
LS2-9665U-40	65W	4000K
LS2-9665U-50	65W	5000K
LS2-9690U-40	90W	4000K
LS2-9690U-50	90W	5000K

*Please contact your MaxLite representative to order products that don't have order codes listed here.

ACCESSORIES			
ORDER CODE	MODEL NUMBER	DESCRIPTION	ACCESSORY IMAGE
74138	MLCHKLSU15	Cable Kit 15' Loop X Toggle Y 1 Pair	
108133	RMHYTHRC-05	Remote Control for MS Commissioning	

SENSOR					
SENSOR	TECHNOLOGY	DIMMING	DAYLIGHT HARVESTING	REMOTE CONTROL	QR CODE
MS	High Frequency	Bi-Level	Set Point	Yes	