

## CEILING FLUSH MOUNT

LED INTEGRATED




PUFF



ARCHITECTURAL



SLIM



DISC/ FAUX CAN



TRADITIONAL



PEARL



### PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. Built with an integrated LED panel, MaxLite flush mounts produce a high quality of light with superior longevity and energy savings when compared to traditional sources. The series is available in nickel, white or bronze finishes with a high-transmission glass lens to complement virtually any décor.

### FEATURES:

- ETL listed for damp locations
- Voltage / Frequency: 120V, Triac Dimming, 60 Hz
- CRI: ≥80 or ≥90 available
- Operating temperature: -4°F to 104°F (-20°C to 40°C)
- Rated Life: L70 ≥50,000 Hours
- Construction: Die formed steel
- Powder coat finish

### WARRANTY:

5-year standard warranty\* (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))

\*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

## PUFF



WATTAGE	18W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1440	1950
Efficacy (lm/W @ 2700K, 80CRI)	80	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1408691	ML2LAMPWH18827
100703	ML2LALPWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT	OPTIONS
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 4.0"H	P= Puff	WH= White	[BLANK]= 120V Triac dimming	18= 18W	8= 80CRI 9= 90CRI <sup>1</sup>	27= 2700K 30= 3000K	J= JA8 Compliant <sup>2</sup>
		L= Large, 16"D x 42"H				24= 24W			

<sup>1</sup> Consult factory for lead times and order quantities

<sup>2</sup> JA8 compliance available in 90CRI, 14W, 11"D x 3.15"H model only. Consult factory for lead time and order quantities.

**ARCHITECTURAL**



WATTAGE	22W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1600	1950
Efficacy (lm/W @ 2700K, 80CRI)	73	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1410232	ML2LAMABN22830
1409612	ML2LALABN24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 14.2" D x 3.5"H	A= Architectural	BN= Brushed Nickel	[BLANK]= 120V Triac dimming	22= 22W	8= 80CRI 9= 90CRI <sup>1</sup>	27= 2700K <sup>1</sup>
		L= Large, 16.1"D x 8.4"H				24= 24W		30= 3000K

<sup>1</sup> Consult factory for lead times and order quantities

**SLIM**




WATTAGE	12W	15W	24W
Sourced lumen (lm @ 3000K, 80CRI)	875	1054	1650
Efficacy (lm/W @ 3000K, 80CRI)	70	70	69

STOCKED ITEMS	
ORDER CODE	CATALOG NUMBER
1410130	ML2L11SLN1230
1410132	ML2L13SLN1530
1410134	ML2L15SLN2430

FAMILY	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CCT
ML2L= Ceiling Flush Mount	11= 11", 11.0 D x 1"H	SL= Slim	NI= Nickel	[BLANK]= 120V Triac dimming	12= 12W	30= 3000K
	13= 13", 13.0 D x 1"H		WH= White		15= 15W	
	15= 15", 14.9"D x 1"H		24= 24W			

**DISC/ FAUX CAN**



SIZE	4"	6"	7"
Delivered lumen (lm @ 2700K, 80CRI)	631	950	1050
Efficacy (lm/W @ 2700K, 80CRI)	69	85	70

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
14099586	DL409830WH
14099589	DL615830WH
14101760	DL715830WH

FAMILY	SIZE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
DL= Disc Light	4= 4", 4.92" D x 1.33"H	WH= White	[BLANK]= 120V Triac dimming	09= 9W	8= 80CRI	27= 2700K <sup>1</sup>
	6= 6", 5.90"D x 1.33" H			15= 15W		30= 3000K
	7= 7", 7.4"D x 1.33" H			40= 4000K <sup>1</sup>		

<sup>1</sup> Consult factory for lead times and order quantities

**TRADITIONAL**



WATTAGE	18W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1260	1650
Efficacy (lm/W @ 2700K, 80CRI)	70	69

MADE TO ORDER	
ORDER CODE	CATALOG NUMBER
1409610	ML2LAMTRWH18830
1409609	ML2LALTRWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 5.1"H	TR Traditional	WH= White	[BLANK]= 120V Triac dimming	18= 18W	8= 80CRI 9= 90CRI <sup>1</sup>	27= 2700K
		L= Large, 15"D x 5.2"H				24= 24W		30= 3000K

<sup>1</sup> Consult factory for lead times and order quantities

**PEARL**



WATTAGE	16W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1100	1350
Efficacy (lm/W @ 2700K, 80CRI)	69	61

MADE TO ORDER	
ORDER CODE	CATALOG NUMBER
1408700	ML2LAMPRBN16827
1408701	ML2LALPRBN22827

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 4.2"H	PR=	BN= Brushed Nickel	[BLANK]= 120V Triac dimming	16= 16W	8= 80CRI 9= 90CRI	27= 2700K
		L= Large, 15"D x 4.6"H				22= 22W		30= 3000K