

LED HIGH OUTPUT NON - DIMMABLE OMNIDIRECTIONAL A-LAMP A21 and A23 SERIES



26A23



21A21



17A21



PRODUCT DESCRIPTION:

MaxLite's LED High Output Non Dimmable Omnidirectional A-Line lamp replicate true A21 and A23 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

FEATURES:

- 17W, 2,000lm, 125W Inc. replacement
- 21W, 2,600lm, 150W Inc. replacement
- 26W, 3,000-3,200lm, 200W Inc. replacement
- ENERGY STAR certified
- Power factor: ≥ 0.95
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- Volts: 120-277V Universal
- Available in E26 base only
- Suitable for damp locations
- Five year limited warranty

APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces



ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 17A21ND27	
FAMILY	BASE	DIMMABILITY	CCT
17A21 = 17 watts, A21 21A21 = 21 watts, A21 26A23 = 26 watts, A23	(OMIT) = E26	ND = Non-Dimmable	27 = 2700K 30 = 3000K 40 = 4000K 50 = 5000K

SPECIFICATIONS:

		17A21ND27	21A21ND27	26A23ND27
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Power Consumption	17W	21W	26W
	Lumens Delivered	2000	2600	3,000-3,200
	Efficacy (lm/w)	118	118	116-123
	CRI	≥80		
	Color Temperature (CCT)	2700K, 3000K, 4000K, 5000K		
	Lumen Maintenance (L70)	25,000 Hours		
ELECTRICAL	Power Factor	≥0.95		
	Input Voltage	120-277V Universal		
PHYSICAL	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
CERTIFICATION	Certification	Energy Star, FCC		
	Environment	Damp		
	Warranty	5 Year Limited		

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
102733	17A21ND27	★	17	125W Inc.	2000	118	80	2700K	2.55" x 4.92"
102734	17A21ND30	★	17	125W Inc.	2000	118	80	3000K	
102735	17A21ND40	★	17	125W Inc.	2000	118	80	4000K	
102736	17A21ND50	★	17	125W Inc.	2000	118	80	5000K	
102729	21A21ND27	★	21	150W Inc.	2600	118	80	2700K	2.75" x 5.13"
102730	21A21ND30	★	21	150W Inc.	2600	118	80	3000K	
102731	21A21ND40	★	21	150W Inc.	2600	118	80	4000K	
102732	21A21ND50	★	21	150W Inc.	2600	118	80	5000K	
102725	26A23ND27	★	26	200W Inc.	3000	116	80	2700K	3.15" x 5.90"
102726	26A23ND30	★	26	200W Inc.	3200	123	80	3000K	
102727	26A23ND40	★	26	200W Inc.	3200	123	80	4000K	
102728	26A23ND50	★	26	200W Inc.	3200	123	80	5000K	

★ ENERGY STAR Certified

Specifications are subject to change without notice.