

OUTDOOR LANTERN
ML4 SERIES - LAMP INCLUDED



TRADITIONAL



PAGODA



PRODUCT DESCRIPTION:

MaxLite LED Lanterns provide long-lasting illumination and energy cost savings for multi-residential properties. BULB in the Box as well as LED integrated solutions are readily available and provide excellent and uniform light quality.

FEATURES:

- Dusk to Dawn on select models
- DHL Motion Sensor on select models

APPLICATIONS:

- Residential
- Hotel/Motel
- Property Management

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

| MODEL SELECTION (Full list of order codes on pg. 2 & 3) | | Typical order example: ML4LE | | | | |
|---|----------------------|-----------------------------------|-----------------------------|-----------|------------------|---------------------------------|
| FAMILY | TYPE | OUTPUT | STYLE | FINISH | CCT/ CRI | CONTROLS |
| ML4= Lanterns | [L] E= Edison Base | 109= 1 x 09W, 60W Inc Equivalent | SP= Traditional | BK= Black | 2= 2700K, 80CRI | |
| | | 121= 1 x 12W, 75W Inc Equivalent | PL= Pagoda | | 27= 2700K, 90CRI | {BLANK}= Dusk to Dawn Photocell |
| | | 171= 1 x 17W, 100W Inc Equivalent | RL= Traditional with Sensor | | 27= 2700K, 90CRI | MSC-V3= DHL Motion Sensor |

SPECIFICATIONS:

| ITEM | SPECIFICATION | DETAILS | | |
|----------------------------|------------------------|--------------------------------|---|---|
| | | 101309 ML4LE109SPLBK2 | 101077 ML4E121PLBK27 | 1408640 ML4LE171RLBK27MSC-V3 |
| GENERAL PERFORMANCE | Power Consumption (W) | 9W | 12W | 17W |
| | Delivered Lumens | 551 lm | 1,150 lm | 1,600 lm |
| | Efficacy (lm/W) | 88.9 lm/W | 96 lm/W | 94 lm/W |
| | L70 Lumen Maintenance | 25,000 hours | | |
| | Dimming | Non Dimmable | | Triac Dimming |
| ELECTRICAL | Input Voltage | 120V, 60Hz | | |
| | Power Factor | ≥ 0.8 | ≥ 0.9 | |
| PHYSICAL | Housing | Die Casting | | Formed Steel |
| | Lens | Frosted Glass | Plastic | Glass |
| | Dimensions (L x W x H) | 4.5"L x 5.75"W x 8.5"H | 6"L x 7"W X10"H | 4.5" X 5.75", 8.5" |
| | Finish | Powder Coat Finish | Black and White | |
| | Operating Temperature | 32°F to 104°F | | 0°F to 104°F |
| | Mounting | J-Box on a Cross Mounted Bar | | |
| CERTIFICATION | Certification | cETLus Damp locations, ES, FCC | cULus wet locations, Energy Star, JA8 Compliant bulb, FCC | cETLus Damp locations, Energy Star, FCC, JA8 Compliant bulb |
| | Warranty | 5 year warranty* | | |