

Torchiere

ML1 SERIES - BULB IN BOX



PRODUCT DESCRIPTION:

LED Torchieres provide long-lasting illumination and energy cost savings for general and accent lighting applications. Offered in black, silver, or white finish, the Torchiere has a half shade that provides even illumination and a die cast steel body ensures enduring style and durability. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

FEATURES:

- Half shade diffuser
- 3-way switch
- Even distribution of light
- CRI: ≥90
- Flicker free bulb included (E26 Base) [Supports Compliance of JA8-2016-E & CEC T20 2016]
- Dedicated voltage 120V, 60Hz
- Five-year limited warranty
- Operating Temperature 0°F to 104°F

CONSTRUCTION:

- Steel construction
- Powder coat finish
- Glass half shade

ORDERING:

ORDER CODE	MODEL NUMBER	ITEM DESCRIPTION
1408628	ML1E2223ARBK27	TORCHIERE ARCHITECTURE BLACK FINISH WITH 10+12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP
1408629	ML1E2223ARWH27	TORCHIERE ARCHITECTURE WHITE FINISH WITH 10+12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP
1408630	ML1E2223ARNI27	TORCHIERE ARCHITECTURE NICKEL FINISH WITH 10+12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP

SPECIFICATIONS:

		ML1E2223ARBK27	ML1E2223ARWH27	ML1E2223ARNI27
ITEM	SPECIFICATION			
GENERAL PERFORMANCE	Power Consumption (W)	22 (1 x 10, 1 x 12)	22 (1 x 10, 1 x 12)	22 (1 x 10, 1 x 12)
	Source Lumens	2,150	2,150	2,150
	Efficacy (lm/W)	98	98	98
	Color Temperature (K)	2700K		
	CRI	≥90		
	L70 Lumen Maintenance	25,000 hours		
ELECTRICAL	Input Voltage	120V		
	Input Frequency	60Hz		
	Power Factor	≥0.9		
PHYSICAL	Dimensions (L x W x H)	10" x 10" x 70"		
	Finish	Black, White, Brushed Nickel		
	Operating Temperature	0°F to 104°F		
CERTIFICATION	Environment	Suitable for Damp Locations		
	Certification	Energy Star, ETL, FCC		
	Warranty	5 year limited warranty		